

Product Brochure

(Top Coat Agents)

06 TOP COAT AGENTS







PRODUCT INTRODUCTION / SPECIFICATIONS

MESG's Top Coat Agents is one of the most refined and flexible for usage in the industry.

These additives added to our topcoat allow users to have an added option of a matte, anti-slip finish, or both.

It also allows for added protection due to its thick and gritty characteristics in extreme environments where added scratch, traction, and damage control are desired.

- Scuff and Abrasion Resistant
- Superior Hardness
- Narrow Particle Distribution
- Highly Chemical Resistant
- Highly Impact Resistant



APPLICATION



WHAT CAN IT BE USED IN?

Below are a few examples:

- Polyurethane
- All Epoxy
- Paints & Varnishes
- Structured Paint
- Road Marking Paint

HOW MUCH DO YOU NEED?

Matte: 6% of Part A & B

Gloss Anti-Slip: 2% of Part A & B Matte Anti-Slip: 4% Anti-Slip + 6%

Matte of Part A & B



HOW TO MIX





WHEN MIXING INTO TOP COAT

Pre-mix the Agents in Part A Top Coat before adding Part B. This will minimize mixing time once Part B (hardener) is added.

Mix until all the agents are blended into Part A.

NOTE:

Add the Part B (hardener) when you're ready to apply.



Headquarters

3 Ang Mo Kio Street 62, Link@AMK, #01-28, Singapore 569139

Phone: (+65) 8788 6565 / (+65) 6902 3188

Fax: (+65) 6983 4388

Support@mesgshop.com

www.mesgshop.com

